


Order no. 863/8900

Tandem three-way tipper and low loader, with inserted aluminium loading rails

Weights:	Total weight of which drawbar load Payload in standard equipment approx. empty weight approx.	8900 kg 500 kg 6450 kg 2450 kg
Dimensions:	Loading dimension inside approx. (length x width) Dropside height approx. loading height unloaded approx. drawbar length approx. coupling height unloaded approx. overall dimensions length x width approx.	4500 x 2300 mm 400 mm 880 mm 1800 mm max. approx. 1020 mm 6550 x 2450 mm
Ramps:	Length approx. width approx. drive-up angle approx.	3300 mm 400 mm 15° Degree
Hydraulics:	Tilt angle rear/side approx. oil requirement approx.	45°/45° Degree 9,0 litres
Tyres:	Size	215/75 R 17.5 4-times with valve sensors for TPMS



Equipped as standard with:

- HARDOX floor grade 450
- EBS brake system with automatic parking brake (TEM) and spring-loaded brake
- Tyre pressure monitoring system (RDK/TPMS)
- Aluminium loading rails with 8t load capacity, inserted under the cargo bed, with locking flap (lockable)
- 3 pairs of lashing points on each side of the cargo bed
- Lighting built into the underride guard
- Painted in two colours in the RAL shade of your choice

Technical description

Order no. 863/8900

Tandem three-way tipper and low loader, with inserted aluminium loading rails

Axles:	GFA high-speed axles with S-cam brake, leaf spring unit with load equalisation
Brake system:	EBS air brake system (multi-voltage with 24V plug-in connection in accordance with ISO 7638-01) with TEM (automatic parking brake), test connections, connecting hoses with interchangeable coupling heads and spring-loaded brake
Pulling device:	Drawbar made of hot-finished S355 grade hollow section, infinitely height-adjustable via spindle winch (12t load capacity), with lorry DIN drawbar eye (40mm), height adjustable from approx. 0.72m to 1.02m
Chassis:	Robust welded construction made of sectional steel (including IPE and UNP profiles grade S355), electrically welded, reinforced underride guard in accordance with ECE R58-03
Structure:	Bridge floor made of one sheet of HARDOX® steel grade 450 ; stable tilting frame with 4 spherical half shells (noise-damped); laser-welded steel drop sides made of fine-grained steel all round and hinged at the sides with strong hinges; swinging rear drop side; plug-in corner posts at the rear; 1 pair of lashing troughs (2500daN) incorporated in the floor, lashing hooks (4000daN) welded onto the front corners, lashing rings (4000daN) welded onto the rear corners
Hydraulics:	Motor-hydraulic; with a heavy 4-stage tilt cylinder and lift limiter; plug-in coupling as single-circuit connection
Support:	One geared support winch with load and high-speed gear at the front; 2 telescopic parking supports with support leg safety device at the rear
Ramps:	Aluminium loading rails, slide in under the loading area; extendable on castors; can be closed with a sturdy steel flap; load capacity/pair 8000 kg; weight approx. 56 kg per unit
Electrics:	Splash-proof lighting in accordance with ECE Directive ECE-R 48.06 (multi-chamber light, protected in the underride guard, LED side marker, clearance and licence plate lights); 24 volt, 7+7 or 15-pin as specified
Paintwork:	Steel parts steel grit blasted, pre-treatment with iron phosphating; corrosion-inhibiting zinc phosphate primer, electrostatic painting in two acrylic RAL colours (high-solid) as specified, subsequent cavity sealing with preservative wax
Accessories:	Tyre pressure monitoring system (TPMS) , 2 brake pads with holder; anti-spray mats, EC type approval; registration papers